

CT18.03LL

Infrared Radiation Thermometer CT18.03LL

for Non-Contact Temperature Measurement

- Rugged stainless steel housing, IP65
- Wide temperature ranges from **500 °C to 3000 °C**
- Very fast response times ≥ 1 ms (programmable)
- Fields-of-view as small as **0.9 mm**
- Laser aims the center and the size of the field-of-view in focus



GENERAL SPECIFICATION

Temperature ranges:	<ul style="list-style-type: none"> ■ <input type="checkbox"/> 500 °C to 1400 °C, <input type="checkbox"/> 550 °C to 1800 °C, <input checked="" type="checkbox"/> 650 °C to 2200 °C, <input type="checkbox"/> 700 °C to 2500 °C, <input type="checkbox"/> 750 °C to 3000 °C
Temperature resolution (NETD):	<ul style="list-style-type: none"> ■ Depends on measured temperature and response time, typical value 0.1 °C (at 100 ms, 350 °C, $\epsilon=1$)
Accuracy:	<ul style="list-style-type: none"> ■ 0.1 °C \pm < 0.4% of the measured value in temperature units at an ambient temperature of 25 °C for the given temperature range
Temperature drift:	<ul style="list-style-type: none"> ■ 0.004% of the measured temperature where the internal temperature of the radiation thermometer deviates from 25 °C
Long term stability:	<ul style="list-style-type: none"> ■ Better than 0.01% of the absolute measured value per month
Spectral response:	<ul style="list-style-type: none"> ■ 0.95 μm
Programmable functions via serial interface:	<ul style="list-style-type: none"> ■ Emissivity, environmental temperature, analog output, function of analog output, response time, temperature unit, valley/peak picker with decay function, reset after time, laser function, alarm values and output
Emissivity:	<ul style="list-style-type: none"> ■ 0.050 to 1.000 in 0.001-steps
Response time:	<ul style="list-style-type: none"> ■ From 1 ms to 10 s (0.001, 0.003, 0.01, 0.03, 0.1, 0.3, 1, 3, 10 s)
Temperature unit:	<ul style="list-style-type: none"> ■ °C, K or °F
Analog output (Hardware):	<ul style="list-style-type: none"> ■ Linear 0 - 20 mA or 4 - 20 mA or 0 – 10 V scalable temperature span ≥ 200 °C
Analog output (Functions):	<ul style="list-style-type: none"> ■ Actual value, max-value or min-value
Analog output (Resolution):	<ul style="list-style-type: none"> ■ 16 bit
Valley/peak picker programmable:	<ul style="list-style-type: none"> ■ Reset: internal ■ Reset: external input ■ Reset: after time (programmable)
Serial interface:	<ul style="list-style-type: none"> ■ RS232-interface, bi-directional, 9.6 kbps to 230 kbps and RS485 interface, Half-Duplex or Full-Duplex, 9.6 kbps to 230 kbps for programming and data transfer
Alarm output:	<ul style="list-style-type: none"> ■ Programmable dry contact (relay)
Operating voltage:	<ul style="list-style-type: none"> ■ 10.5 VDC to 30 VDC
Power consumption:	<ul style="list-style-type: none"> ■ ≤ 2.5 W
Permissible ambient temperature:	<ul style="list-style-type: none"> ■ -20 °C to 70 °C <input type="checkbox"/> With protective and cooling housing WK15 up to 300 °C
Storage temperature:	<ul style="list-style-type: none"> ■ -20 °C to 80 °C
Protective class:	<ul style="list-style-type: none"> ■ IP65 (IEC), (NEMA 4 equivalent)
Housing:	<ul style="list-style-type: none"> ■ Stainless steel
PC-based Software:	<ul style="list-style-type: none"> ■ EasyConfig: Software for parameter setting <input type="checkbox"/> EasyMeas: Software for parameter setting, data recording, data storage and data evaluation

<ul style="list-style-type: none"> ■ Standard function <input type="checkbox"/> Option
--


CT18.03LL

OPTICS

Fibre optic with objective (lens)

- Objectives (Lenses):** ■ Focusable from 45 mm to infinity
- Field of view diameter:** ■ From \varnothing 0.9 mm, depends on lens
- Field of view marking:** □ Laser built-in: aims the center and the size of the field of view in focus
- Laser function:** □ Time out or permanent operation, while flashing or continuous marking
- Permissible ambient temperature:** □ -25 °C to 200 °C
- Protective class:** □ IP54

DIMENSIONS



Dimensions in mm

ACCESSORIES



Protective and cooling housing WK15



Protective and cooling housing with airpurg and extension tube